



VCXO LVPECL Differential Oscillator
VCXO7050PW3.3 3.3V

- SMD in ceramic case (7.0 x 5.0 x 1.8) mm
- LVPECL Square Wave Output Wave Form
- High Q fundamental crystal + multiplier circuit
- RoHS conform; Lead-free product
- Vibration: MIL-STD-202F method 204, 35G, 50 to 2000 Hz
- Shock: MIL-STD-202F method 213B, test cond. E, 1000GG 1/2 sine wave
- Available in many standard and special frequencies



Specifications

Holder Type:	VCXO LVPECL Differential Oscillator VCXO7050PW3.3 3.3V (Voltage code is "3.3"); Tri-State on pad 2
Frequency Range:	750 kHz to 800 MHz
Frequency Stability at 25°C:	±20 to ±100 ppm
Operating Temperature Range:	±20 to ±100 ppm, -20°C to +70°C, -40°C to +85°C
Frequency Deviation:	±100ppm (typ.), ±150ppm
Storage Temperature:	-55°C to +150°C
Power Supply Voltage (Vdd):	+ 3.3V D.C. ± 5%
Maximum Supply Current (15pF load):	25mA max. (< 24MHz), 65mA max. (24.01MHz ~ 96.00MHz) 100mA max. (96.01MHz ~ 800.00MHz)
Load:	RL= 50 for (Vdd-2.0V)
Output Logic Levels:	High "1" Voh Vdd-1.025min., -0.95typ., -0.88max.; RL= 50 to (Vdd-2.0V) Low "0" Vol Vdd-1.810min., -1.70typ., -1.62max.; RL= 50 to (Vdd-2.0V)
Output Symmetry (Duty Cycle):	50% ± 5% max. @ Vdd-1.3V
Voltage Control:	1.65V DC Center / 0.3V to 3.0V Range
Rise/Fall Time:	1.5ns max. @ 20% to 80% of PECL wave form
Start Up Time:	10 ms max.
Tri-state Function Pin 2:	When Pin 2 = 1, Output Enable When Pin 2 (at 0.0V), Output High impedance, Disable current: 50µA max.
Phase Jitter (12 kHz to 20 MHz):	2.6 ps typ., 4ps max., for 155.520MHz
Phase Noise (155.520 MHz):	-60dBc/Hz @ 10Hz, -90dBc/Hz @ 100Hz, -115dBc/Hz @ 1kHz -125dBc/Hz @ 10kHz, -119dBc/Hz @ 100kHz, -120dBc/Hz @ 1MHz
Aging:	< ±3ppm max. for the first year
Input Impedance:	2 M (min.)
Reflow Condition:	260°C max for 10 sec.

GERMANY:

COMTEC CRYSTALS GmbH · Sultenstrasse 12-14
8 5 5 8 6 P o i n g / G E R M A N Y
Phone +49 8121 778160 · Fax +49 8121 778177
e-Mail info@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Subject to change without prior notice.



Technical Data and Graphics are all under
Copyright (c) of Comtec Crystals Group.

FRANCE:

COMTEC CRYSTALS SARL · 23, rue du Faucon
6 7 5 0 0 H a g u e n a u / F R A N C E
Phone +33 388 732162 · Fax +33 388 730118
e-Mail sales@comtec-crystals.com
Internet: <http://www.comtec-crystals.com>
Sous réserve de modifications.